



FOTON

0878-7070-1398

www.foton-indomobil.com



AUMAN EST
8x4 380HP

EST 8x4 - 380HP DUMP TRUCK

Main Parameter		
Complete vehicle dimension parameters	Wheelbase (mm)	1800+4700+1350
	Chassis Dimensions(LxWxH) (mm)	11592×2545×3475
	Inner Cargo Body(LxWxH) (mm)	8600×2300×1800/2000
Complete vehicle mass parameter	Chassis kerb mass (kg)	13500
	Designed payload (kg)	60000
	GVW (Design) (kg)	80000
Complete vehicle performance parameter	Maximum speed (km/h)	95(5.26)、105(4.76)、85(5.92)
	Maximum climbing capacity, % (full load)	34(5.26)、30(4.76)、39(5.92)
Product configuration		
Engine	Model	Cummins ISG-380
	Displacement (mL)	11800
	Rated power (ps/rpm)	380/1900
	Maximum output torque(Nm/rpm)	2000/1000-1300
Gearbox	Model	12JSD180TA (Q)
	Speed control mode	Manual
Front axle	Rated load	9.5T
	Brake type	Drum
Rear axle	Model/Axle housing type	Double reduction/Casting
	Rated load/speed ratio	16T/5.92
	Brake type	Drum
Suspension	Front suspension/spring number	Vertical leaf spring + barrel shock absorber/13/14
	Rear suspension/spring number	Longitudinal leaf spring type balance shaft suspension, frame type balance shaft/12
Tire	Specification	12.00R20
	Quantity	12+1
Brake	Service brake	Dual circuits pneumatic drum brake
	Parking brake	Spring actuated air cut-off parking brake
	Auxiliary brake	iBrake braking (Engine Brake)
	ABS	Optional
Fuel tank	Specification and material	350L
Other Configurations	Cab suspension	Half floating airbag
	Cab lifting	Electric control
	Seat type	Airbag seats
	AC	Standard

Note: FOTON reserves the right to make changes in the specifications and other information contained in this document without prior notification

GERMAN QUALITY 

MONEY MASTER



Contact:

PT. Foton Pemasaran & Penjualan Indonesia

+62 81340610050

huoxianqiang2@foton.com.cn

www.foton-global.com

