



FOTON

0878-7070-1398

www.foton-indomobil.com



AUMANEST
6x4 380HP

EST 6x4 - 380HP EURO 4 DUMP TRUCK

Main Parameter		
Vehicle Dimensions	Wheelbase (mm)	4100+1400
	Overall Dimensions (LxWxH) (mm)	8800x2500x3800
	Chassis Dimensions (LxWxH) (mm)	7900x2500x3360
	Cargo Body Dimensions (mm)	6000x2300x1000
Vehicle Weight	Chassis kerb weight (Kg)	10800
	Designed payload (Kg)	17200
	GVW (Kg)	28000
Vehicle Performance	Maximum Speed (Km/h)	75(4.76)/70(5.26)/62(5.92)
	Max. Climbing Capacity % (full load)	31(4.76)/34 (5.26)/40(5.92)
Product configuration		
Engine	Model	Cummins ISGe4-380
	Displacement (ml)	11800
	Rated power (ps/rpm)	380/1900
	Maximum output torque(Nm/rpm)	2000/1000-1300
Gearbox	Brand/Model	Manual HW23712 with PTO
Front axle	Rated load	6T
	Brake type	Drum Brake
Rear axle	Model/Housing Type	Double Reduction/Casting
	Rated load/Speed ratio	11T / 5.26
	Brake type	Drum Brake
Suspension	Front Suspension	Longitudinal Multi-leaf Steel Spring + Telescopic Shock Absorber
	Rear suspension	Integral balanced suspension + longitudinal plate spring
Tire	Specification	12.00R20
	Quantity	10+1
Brake	Service brake	Dual Circuits Pneumatic Drum Brake
	Parking brake	Spring Actuated Air Cut-off Parking Brake
	Auxiliary brake	iBrake braking (Engine Brake)
Fuel tank	Specification and Material	350L
Other Configurations		Half Floating Airbag Cabin Suspension, Electric Cabin Lifting, Airbag Seat, and A/C

Note: FOTON reserves the right to make changes in the specifications and other information contained in this document without prior notification

GERMAN QUALITY 

MONEY MASTER



PT. Foton Pemasaran & Penjualan Indonesia

+62 81340610050

huoxianqiang2@foton.com.cn

www.foton-global.com



Contact:

Technology leading into the future.