



0878-7070-1398
www.foton-indomobil.com

EVolve a Better World



Swift acceleration



High speed



Fast charging



Quick profitability



Prompt service

Electric



MODEL

TRUCK MATE (EWF3-2.5)

Specification

Steering Wheel position	Right
GVW (kg)	2540
Curb weight (kg)	1520
Payload (kg)	1020
Wheelbase	2600
Vehicle dimensions (mm)	4670×1590/1860
Cargo compartment dimensions (mm)	3050×1560×360/1570
Driving mileage per charge * (km)	220(NEDC)
Brake system	hydraulic brakes

Battery

Battery supplier	CATL
Type of the battery	LFP
Capacity of the battery (kwh)	38.64
Voltage (V)	309.12
Charging mode	DC/AC
Charging time (20°C) SOC0%-100%	1h/6h
Charging time (20°C) SOC20%-80%	0.5h/4h

Motor

Motor type	Permanent magnet synchronous motor
Rated/peak power (kW)	30/60
Rated/peak torque (N.m)	100/220

Basic equipment

ABS	●
EBD	●
AC	●
Deflector	○

PERFORMANCE

EASY MOVE

60kW high-power motor, fast acceleration. Turning radius of 4.9m, freely maneuver through streets and alleys.

FAST CHARGING

Charging can be completed during a short break, presenting a full range of 220 kilometers.

SUPER LOAD CAPACITY

Adopting high-strength materials, reinforced with double-layer steel plates in key areas. Equipped with a 3050 cargo tank for stronger load capacity.

SAFETY AND RELIABILITY

Using lithium iron phosphate batteries for higher safety factor and longer cycle life. Equipped with ABS+EBD as standard, upgraded with 11 safety configurations, and validated for reliability over a million kilometers.

WORRY-FREE THROUGHOUT THE JOURNEY

5-year warranty for the motor, battery and electronic control system, responsive localized service mode.

PT Indomobil Global Transportasi



[Redacted phone number]



[Redacted email address]



[Redacted website]



2 YEAR
WARRANTY / 50,000 KM