



0878-7070-1398
www.foton-indomobil.com

e AUMARK

EVOLVE A BETTER WORLD



14 T

SPECIFICATIONS		
Basic information	Cab	Single row
	Driving type	4×2
	Cab-by the number	3
	Steering wheel position	RHD
Mass	Gross Vehicle Weight (G.V.W.)	14000
	Curb weight-chassis	4768
Dimension	Dimension (Chassis)	7365×2130×2360
	Cargo (closed)	5500×2350×2300
	Wheelbase	4200
	Wheel Tread (Front / Rear)	1832/1820
Performance	Maximum Speed	90
	Grade Ability	24%
	Range	204 (C-WTVC, 25°C)
Motor	Motor Type	Permanent magnet synchronous motor
	Torque Rated/Peak	135/260
	Torque Rated/Peak	2800
Battery system	Battery Composition Material	LFP
	Capacity	162
	Voltage	540.96V
	Cooling type	Liquid cooling
	Charge mode	CCS2 DC
	Charging Time (20°C) SOC 20%~80%	DC:1.2h
Brake	Brake	Pneumatic brake
	Front brake	Drum
	Rear brake	Drum



Advanced configuration

- ◆ EPB+ASR+CCS to ensure comfortable driving



Dynamic performance

- ◆ Equipped with a super-power direct-drive motor, with peak power of 260 kW and peak torque of 2800 N·m, maximum gradeability more than 20%



Safety performance

- ◆ Equipped with CATL battery, safe and reliable. The whole vehicle has completed reliability verification for over 300,000 km, with low risk of thermal runaway
- ◆ Driving safety: equipped with ABS, optional driver and passenger airbags to providing driving protection



Range

- ◆ 162.28 kW·h battery with high energy density, long life, long endurance and good low-temperature performance with a range of up to 200 km, and fast-charging replenishment within



Modification performance

- ◆ Equipped with a continuous output power of 20 kW power outlet, can be used for urban logistics and distribution, refrigerated transportation, urban sanitation and other scenarios

Edwin Foton Truck

Contact: 085715690773

WEB : <https://sites.google.com/view/fotontrukindonesia/home>

FOTON authorized distributors



PT. Indomobil Global Transportasi
@fotonindonesia